(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the limitation. See text for further explanation of ratings in this table.)

Print date: 08/23/2002

Map symbol and soil name	of			 Suitability for log landings 		Soil rutting hazard 	
		Rating class and limiting features		Rating class and limiting features		Rating class and limiting features	
Cb: Coastal Beaches	70	 Not rated 	 	 Not rated 		 Not rated 	
DoA: Downer	 100 	 Slight 	 	 Well suited 		 Moderate Strength 	0.50
DoB: Downer	100	 Slight 	 	 Well suited 		 Moderate Strength	0.50
DoC: Downer	100	 Slight 	 	 Moderately suited Slope	0.50	 Moderate Strength	0.50
DoC3: Downer	100	 Slight 	 	 Moderately suited Slope	0.50	 Moderate Strength	0.50
Fa: Fallsington		 Moderate Strength 	0.50	Wetness	11.00		1.00
Fb: Fallsington	100	 Moderate Strength 	0.50	 Poorly suited Wetness Strength	11.00		1.00
FdA: Dragston		 Moderate Strength	 0.50	 Moderately suited Strength Wetness	0.50	 Severe Strength	1.00
Fallsington		 Moderate Strength 	0.50	 Poorly suited Wetness Strength	 1.00 0.50	 Severe Strength 	11.00
FdB: Dragston		 Moderate Strength 	 0.50	 Moderately suited Strength Wetness	 0.50 0.50	Strength	1.00
Fallsington	 50 	 Moderate Strength 	 0.50 		11.00	Strength	1.00

Table FOR-1.--Forestland Management--Continued

and soil name	of map	Limitations affecting Suitability for construction of log landings haul roads and log landings		Soil rutting hazard 			
	 			Rating class and limiting features			
FgA: Dragston		 Moderate Strength 	 0.50	 Moderately suited Strength Wetness	 0.50 0.50	 Severe Strength 	1.00
Fallsington		 Moderate Strength 	0.50	 Poorly suited Wetness Strength	11.00	 Severe Strength 	1.00
FgB: Dragston		 Moderate Strength 	 0.50	 Moderately suited Strength Wetness	 0.50 0.50	 Severe Strength 	1.00
Fallsington		 Moderate Strength 	 0.50	 Poorly suited Wetness Strength	1 1.00	 Severe Strength 	1.00
GcB: Galestown	 100 	 Moderate Sandiness 	 0.50	 Moderately suited Sandiness	 0.50	 Moderate Strength 	0.50
GlB: Galestown		 Moderate Sandiness	0.50	 Moderately suited Sandiness	0.50	 Moderate Strength	0.50
Lakeland			0.50	 Moderately suited Sandiness	0.50	 Moderate Strength	0.50
GlC: Galestown	 50 	 Moderate Sandiness 	 0.50	 Moderately suited Sandiness Slope	 0.50 0.50	 Moderate Strength 	0.50
Lakeland		 Moderate Sandiness 	 0.50 	 Moderately suited Sandiness Slope	 0.50 0.50	 Moderate Strength 	0.50
<pre>Gp: Gravel And Borrow Pi</pre>	 100 	 Not rated 	 	 Not rated 		 Not rated 	
Jo: Johnston Loam	 100 	 Not rated 	 	 Not rated 	 	 Not rated 	
KfA: Keyport	 95 	 Slight 	 	 Well suited 	 	 Moderate Strength	0.50
KmA: Keyport	 95 	 Moderate Strength 	0.50	 Moderately suited Strength 	0.50	 Severe Strength 	1.00

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	of map	Limitations affecting construction of haul roads and log landings		Suitability for log landings 		Soil rutting hazard 	
	 			Rating class and limiting features			
KnA: Klej	 95 	 Slight 	 	 Moderately suited Wetness	0.50	 Moderate Strength	0.50
KnB: Klej	95	 Slight 	 	 Moderately suited Wetness	0.50	 Moderate Strength	0.50
LaB: Lakeland			 0.50	 Moderately suited Sandiness 	 0.50	 Moderate Strength 	0.50
LgB: Lakeland		 Moderate Sandiness	0.50	 Moderately suited Sandiness	0.50	 Moderate Strength	0.50
Galestown		 Moderate Sandiness	0.50	 Moderately suited Sandiness	0.50	 Moderate Strength	0.50
LmC: Lakeland	50	 Moderate Sandiness 	 0.50	 Moderately suited Sandiness Slope	 0.50 0.50	 Moderate Strength 	0.50
Galestown			 0.50	 Moderately suited Sandiness Slope	10.50	 Moderate Strength 	0.50
Lo: Leon	100	 Moderate Sandiness 	0.50	 Moderately suited Wetness Sandiness	0.50	Strength	0.50
Ma: Made Land	100	 Not rated	i I	 Not rated 		 Not rated 	
MfA: Matapeake	100	 Slight 	 	 Well suited 		 Moderate Strength 	0.50
MfB2: Matapeake	100	 Slight 	 	 Well suited 		 Moderate Strength	0.50
MfC: Matapeake	100	 Slight 	 	 Moderately suited Slope	0.50	 Moderate Strength	0.50
MkA: Matapeake	100	 Moderate Strength	 0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
MkB2: Matapeake	100	 Moderate Strength 	0.50	 Moderately suited Strength 	0.50	 Severe Strength 	1.00

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	of map	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard 	
	 			Rating class and limiting features			
MkC2: Matapeake		 Moderate Strength 	0.50	 Moderately suited Strength Slope	 0.50 0.50	 Severe Strength	1.00
MkC3: Matapeake		 Moderate Strength 	0.50	 Moderately suited Strength Slope	 0.50 0.50	 Severe Strength 	1.00
MkD: Matapeake		 Moderate Strength 	0.50	 - Poorly suited Slope Strength	11.00	 Severe Strength	1.00
MpA: Mattapex		 Moderate Strength	0.50	 Moderately suited Strength	 0.50	 Severe Strength	1.00
MpB2: Mattapex		 Moderate Strength	0.50	 Moderately suited Strength	 0.50	 Severe Strength	1.00
MsA: Mattapex		 Moderate Strength	0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
MsB2: Mattapex		 Moderate Strength	0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
Mx: Mixed Alluvial Land-	 70 	 Not rated 	 	 Not rated 	 	 Not rated 	
My: Muck And Peat	 100 	 - - Not rated -	 	 - - Not rated -	 	 - Not rated -	
OhA: Othello		 Moderate Strength 	 0.50	 - Poorly suited Wetness Strength	 1.00 0.50	 Severe Strength 	1.00
OhB2: Othello	95 	 Moderate Strength 	 0.50	 Poorly suited Wetness Strength	 1.00 0.50	 Severe Strength 	1.00
Om: Othello	 100 	 Moderate Strength 	 0.50	 Poorly suited Wetness Strength 	 1.00 0.50	 Severe Strength 	1.00

Table FOR-1.--Forestland Management--Continued

and soil name of				 Suitability for log landings 		 Soil rutting hazard 	
	 			Rating class and limiting features			Value
Oo: Othello	100			Wetness			1.00
Os: Othello		 Moderate Strength		Wetness	11.00		1.00
Ot: Othello	100			Wetness			1.00
Pd: Plummer	100	 Slight 				 Moderate Strength	0.50
Pk: Pocomoke	100	 Moderate Strength		Wetness			1.00
Pm: Pocomoke	100			Wetness			1.00
Po: Portsmouth		 Moderate Strength	0.50	Wetness	11.00		1.00
Pr: Portsmouth		 Moderate Strength		Wetness			1.00
Sa: St Johns	100			Wetness			0.50
SfA: Sassafras	100	 Slight 	 	 Well suited		 Moderate Strength	0.50
SfB2: Sassafras	100	 Slight 	 	 Well suited 		 Moderate Strength	0.50
SfC2: Sassafras	100	 Slight 	 	 Moderately suited Slope 	 0.50	 Moderate Strength 	0.50

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	of map	1		Soil rutting hazard			
	 	Rating class and limiting features		Rating class and limiting features		Rating class and limiting features	
SfC3: Sassafras	100	 Slight 	 	 Moderately suited Slope	 0.50		0.50
SfD: Sassafras	100	 Slight 	 	 Poorly suited Slope	1.00	 Moderate Strength	0.50
St: Steep Sandy Land	100	 Not rated 	 	 Not rated 		 Not rated 	
Sw: Swamp	100	 Not rated 	 	 Not rated 		 Not rated 	
Tm: Tidal Marsh	100	 Not rated 	 	 Not rated 	 	 Not rated 	
WdA: Woodstown			 0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
WdB2: Woodstown	95		 0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
WoA: Woodstown	95		0.50	 Moderately suited Strength	0.50	 Severe Strength	1.00
WoB2: Woodstown	95	 Moderate Strength 	 0.50 	 Moderately suited Strength 	0.50	 Severe Strength 	1.00